



# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

**No.: 2020312310000239**

**Applicant and address**

DNH AS

Gruveveien 2-4, 3770 Kragerø, Norway

**Manufacturer and address**

DNH AS

Gruveveien 2-4, 3770 Kragerø, Norway

**Factory and address**

DNH AS

Gruveveien 2-4, 3770 Kragerø, Norway

**Product, series, specification and model**

Loudspeaker

See annex

Ex db eb IIB+H<sub>2</sub> T6 Gb

**Standards**


GB/T 3836.1-2021, GB/T 3836.2-2021, GB/T 3836.3-2021

**This product(s) complies with the requirements of CNCA-C23-01: 2024  
China Compulsory Certification Implementation Rule on Explosion  
Protected Electrical Product.**

**Issue date: 2025-11-18 Valid to: 2030-11-27**


Detailed information and status of this certificate is available by using the QR code,  
visiting CNEx's website or CNCA's website: [www.cnca.gov.cn](http://www.cnca.gov.cn).

This translated document has no legal effect and shall not be used alone.



Director:

Nanyang Explosion Protected Electrical  
Apparatus Research Institute Co., Ltd.



# CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

No.: 2020312310000239

Annex: Page 1 of 1

## Product information:

### 1. This certificate covers the following models:

- BA-56EExeN(T), BA-56EExeN(T)x2, BA-56EExeN(T)MF, BA-56EExeN(T)-B30

This certificate covers a Ceiling loudspeaker for flush mounting with or without transformer.

"T" in the type designation indicates design with transformer.

"MF" designation for variant model indicates design with moulded e-chamber with permanent cable.

"x2" in the type designation indicates variant with two separate sets of loudspeakers, transformers (optional) and terminals (A+B).

"B30" in the type designation indicates variant with B30 Mounting Kit.

Voltage: 100V, Power: 6W, Freq: 150-20000Hz

IP Code: IP54

Ex marking: Ex db eb IIB+H<sub>2</sub> T6 Gb

- Manufacturer should organize production in accordance with the technical documents approved by the certification body.

### 2. Specific conditions of use:

- Ambient temperature range:  $-20^{\circ}\text{C} \leq T_a \leq +50^{\circ}\text{C}$ .
- Before application, CCC certified cable gland that suitable for the conditions of use and/or stopping plug shall be applied, and correctly installed.
- See instruction for other information.

### 3. Certificate change information:

- This certificate is issued for renewal upon expiration, The first issuance date of the certificate is 2020-11-26.



Nanyang Explosion Protected Electrical  
Apparatus Research Institute Co.,Ltd.

